



VCC-7HD30N

FHD 30x Zoom PTZ Camera

SONY 이미지 모듈 탑재

1/2.8인치 Sony Image Sensor

3G-SDI 출력

1080p, 213만 화소의 선명한 화질

전문가용 고품질 화질 구현

방송, 스튜디오 화질개선 송출용 사용에 적합

Image Stabilizer

미세한 떨림 현상 감소

Feature

| | | | | |
|-------------------------------------|---------------------|---------------------------|----------------------------|------------------------------|
| FHD 1080p60 1080i59.94 | 30X | SONY Image Block | POE+ | 63.7° HOV |
| 3G-SDI | HDMI 1.4 | SD-IP True Dual Output | RGB CPY Color matrix | Image Stabilizer |
| HDMI SDI | LOW LATENCY MODE | SRT READY | FHD IP HEVC | Serial + IP Control |
| SMPTE | VISCA | VISCA over IP | RS-232 RS-422 RS-485 | Onvif |
| RTSP RTMP | Audio SDI/HDMI | FELCO P/D | VISCA over IP | |

Specification

| | |
|---------------------------------|--|
| Image Sensor | 1/2.8인치 Exmor R CMOS (2.13MP) SONY의 정품 모듈 FCB-EV7520A 탑재 |
| Resolution | 1080p (60, 59.94, 50, 30, 29.97, 25) 1080i (60, 59.94, 50, 30) 720p (60, 59.94, 50, 30, 29.97, 25) |
| Zoom | 광학 30배 디지털 12배줌 |
| Aperture | F1.6(W)~F4.7(T) |
| Horizontal Angle of View | 63.7°(W)~2.3°(T) |
| Focus | Auto Focus Manual Focus One Push Trigger |
| Feature | Image Stabilizer Flip Mirror HLC High Sensitivity Defog mode Backlight Compensation |
| White Balance | Auto Indoor Outdoor OPW ATW Manual |
| Control | RS232/RS-422/RS485 Visca over IP IR Remote Control |
| Interface | 3G-SDI HDMI IP CVBS |
| Control | RS422 IP Control IR Remote Control |
| Size | L160 x W178 x H220mm 2Kg |
| Power | 12V2A DC 15W(Max) POE+ |